



**ECHA**  
Registered

## EffiTab International AB

Folke Bernadottes väg 445  
256 57 Ramlösa  
E-post: office@effitab.com



www.effitab.com

# Gold Fuel Treatment HFO /

For cleaner and more effective combustion

- **Combustion-improving fuel additive solution containing nano-catalyst particles in a proprietary blend of aromatic hydrocarbon solvents.**
- **ECHA and EPA registered.**
- **Contains no sulphur, no phosphorus, nor halogens.**

## PRODUCT DESCRIPTION

- Catalyzes the combustion of hydrocarbon fuels to achieve a more complete burn and prevent engine knock.
- Effective with all grades of heavy fuels.
- Blends readily with fuel for one-step treatment of bulk storage tanks.
- Sublimates after combustion with no harmful by-products, as per ECHA (European Chemical Agency, EU) and EPA (Environmental Protection Agency, USA).
- Does not interact with water shedding properties.
- High purity level will not harm boilers or engines and will not void warranties.
- Will not adversely affect fuel stability, cold-flow properties and bacteria growth.
- Does not interact with fuel colorants and markers.
- Safe to transport, store and handle.

## APPLICATIONS

- Recommended dosage rate is 1 part **EffiTab Gold Fuel Treatment HFO** to 5,000 parts heavy fuel oil (by volume) for continuous usage.
- For initial charging dosage use 1 part **EffiTab Gold Fuel Treatment HFO** to 4,000 parts fuel.
- For use in all grades of residual fuels.
- Treated fuel can be safely burned in boilers and all types of diesel engines.

## BENEFITS

- Reduces fuel consumption, typically by 2 to 5%.
- Reduces diesel particulate emissions by up to 43%.
- Improves combustion efficiency and reduces CO emissions.
- Keeps fuel injectors and turbochargers cleaner and extends oil change intervals.
- Acts as a high temperature lubricant, inhibiting mechanical abrasion to prolong engine life and reduce engine wear.
- Reduces polluting exhaust emissions, including visible black smoke, particulates, CO, NOx and total amount of CO2.
- Reduces maintenance costs and spare parts consumption by preventing soot formation and carbon deposits.
- Improves lubricity with low sulfur fuel.



**ECHA**  
Registered

## EffiTab International AB

Folke Bernadottes väg 445  
256 57 Ramlösa  
E-post: [office@effitab.com](mailto:office@effitab.com)



[www.effitab.com](http://www.effitab.com)

# Gold Fuel Treatment HFO /

For cleaner and more effective combustion

## TYPICAL PHYSICAL PROPERTIES

- Clear, dark yellow liquid
- Aromatic odor
- Specific Gravity: 0.89 @ 20 °C
- Flash Point: 62.8 °C (closed cup)
- Crystallization Point: below -8 °C

## STORAGE AND HANDLING

**EffiTab Gold Fuel Treatment HFO** fuel treatment is readily pumpable and self-feeding into the suction side of a metering pump, from unheated additive storage at temperatures above -20 °F (-29 °C). It is stable in mild steel and in aluminium storage tanks, or when properly stored in its original containers for at least 12 months. It is an industrial chemical and should be handled with the same precautions as used with ordinary distillates, solvents, and weak alkalis. Avoid open flames. Avoid skin and eye contact. Wash contaminated areas with soap and water.

## AVAILABILITY

**EffiTab Gold Fuel Treatment HFO** is available in non-returnable 19 litre barrels and oil drums 205 litres. Product ships from North America to major seaports under HS Tariff Classification Number: 3811.19.00.

*For more information regarding engine performance and technical processes, please contact us at office@effitab.com.*